# Product overview



| | Door | | Frame | | | | | | | Max length wood logs | Interior | | Weight | Output | Gas flue outlet | Air supply | Air box | Convection casing | Convection fan system | Standard | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | modern door | 6-door | frameless | classic frame | insert frame | built-in frame | 3-sided frame 35 mm. | 4-sided frame 35 mm. | Hidden Door+ 8 cm. & stone bar | max. cm. | vermiculite panels | ceramic concrete | kg aprox. | kW | Ø (mm.) | Ø (mm.) | option | standard | optional system | CE - EN 13229 | Flamme Verte | Flamme Verte Indice I' | 1.BImSchV | VKF-LRV11 | Smoke Control Areas | CO (vol%) | fine particles (mg/m³) | efficiency (%) | system efficiency, approx.* (%) | multi-fuel (only available in the UK) | energy efficiency class |
| **Universal-6** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Universal-6 60[1] | | • | • | • | • | • | | | | 35 | | • | 100 | 5-9 | 150 | 125 | | | • | • | ****** | 0,60 | • | • | • | 0,09 | 46 | 78 | 84 | | A |
| Universal-6 65 | | • | • | • | • | • | | | | 35 | | • | 112 | 6-9 | 150 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,07 | 24 | 79 | 84 | | A |
| Universal-6 70 | | • | • | • | • | • | | | | 40 | | • | 115 | 7-10 | 180 | 125 | | | • | • | ******* | 0,50 | • | • | • | 0,09 | 36 | 77 | 84 | | A |
| Universal-6 75 | | • | • | • | • | • | | | | 40 | | • | 126 | 7-11 | 180 | 125 | | | • | • | ******* | 0,50 | • | • | • | 0,09 | 27 | 76 | 83 | | A |
| Universal-6 80 | | • | • | • | • | • | | | | 40 | | • | 128 | 8-12 | 180 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,06 | 27 | 76 | 83 | | A |
| Universal-6 85 | | • | • | • | • | • | | | | 50 | | • | 141 | 8-12 | 180 | 125 | | | • | • | ******* | 0,50 | • | • | • | 0,10 | 20 | 77 | 84 | | A |
| **Unilux-6** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Unilux-6 40 | | • | • | • | • | • | | | | 20 | | • | 68 | 4-6 | 130 | 80 | | | • | • | ******* | 0,50 | • | • | • | 0,08 | 39 | 76 | 83 | • | A |
| Unilux-6 43 | | • | • | • | • | • | | | | 30 | | • | 97 | 6-8 | 130 | 80 | | | • | • | ******* | 0,30 | • | ** | ** | 0,05 | 20 | 79 | 84 | | A |
| Unilux-6 45 | | • | • | • | • | • | | | | 20 | | • | 87 | 5-7 | 130 | 80 | | | • | • | ******* | 0,40 | • | ** | ** | 0,09 | 20 | 76 | 81 | | A |
| Unilux-6 52 | | • | • | • | • | • | | | | 30 | | • | 79 | 5-8 | 130 | 80 | | | • | • | ******* | 0,40 | • | • | • | 0,06 | 34 | 78 | 85 | • | A |
| Unilux-6 55 | | • | • | • | • | • | | | | 30 | | • | 93 | 6-9 | 130 | 80 | | | • | • | ******* | 0,40 | • | • | • | 0,05 | 34 | 75 | 82 | • | A |
| Unilux-6 65 | | • | • | • | • | • | | | | 40 | | • | 90 | 7-9 | 150 | 125 | | | • | • | ******* | 0,60 | • | • | • | 0,08 | 40 | 75 | 82 | • | A |
| Unilux-6 67 | | • | • | • | • | • | | | | 40 | | • | 109 | 7-10 | 150 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,07 | 19 | 75 | 82 | • | A |
| Unilux-6 70 | | • | • | • | • | • | | | | 45 | | • | 105 | 8-12 | 150 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,07 | 25 | 76 | 83 | • | A |
| Unilux-6 75 | | • | • | • | • | • | | | | 50 | | • | 107 | 9-13 | 150 | 125 | | | • | • | ******* | 0,50 | • | • | • | 0,06 | 40 | 75 | 82 | • | A |
| Unilux-6 80 | | • | • | • | • | • | | | | 50 | | • | 123 | 8-11 | 150 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,09 | 17 | 76 | 83 | • | A |
| Unilux-6 265 Left / Right | | • | | • | | • | | | | 40 | | • | 114 | 7-9 | 150 | 125 | | | • | • | ******* | 0,60 | • | ** | ** | 0,10 | 39 | 75 | 82 | | A |
| Unilux-6 265 Three sided | | • | | • | | • | | | | 40 | | • | 112 | 7-9 | 150 | 125 | | | • | • | ******* | 0,60 | • | ** | ** | 0,10 | 39 | 75 | 82 | | A |
| Unilux-6 270 Left / Right | | • | | • | | • | | | | 45 | | • | 138 | 9-12 | 180 | 125 | | | • | • | ******* | 0,40 | • | ** | ** | 0,09 | 19 | 75 | 82 | | A |
| Unilux-6 270 Three sided | | • | | • | | • | | | | 45 | | • | 135 | 9-12 | 180 | 125 | | | • | • | ******* | 0,40 | • | ** | ** | 0,09 | 19 | 75 | 82 | | A |

| | Porte | | Cadre | | | | | | | Taille des bûches | Intérieur | | Poids | Puissance | Diamètre de connexion au conduit | Entrée d'air | Boîte de raccordement | Caisse de convection | Ventilateur de convection | Normes | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | porte moderne | porte 6 | sans cadre | cadre classique | cadre de profondeur | cadre encastrable | 3 côtés 35 mm. | 4 côtés 35 mm. | Hidden Door+ 8 cm. | Hidden Door+ 8 cm. & extérieur en pierre | max. cm. | plaques de vermiculite | béton céramique | kg | kW | Ø (mm.) | Ø (mm.) | option | standard | option | CE - EN 13229 | Flamme Verte | Flamme Verte Indice I' | 1.BImSchV | VKF-LRV11 | Smoke Control Areas | CO (vol%) | poussières fines (mg/m³) | rendement de certification (%) | rendement de système* (%) | multi-combustibles (disponible uniquement au Royaume-Uni) | Classe d'efficacité énergétique |
| **Universal-6** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Universal-6 60[1] | | • | • | • | • | • | | | | 35 | | • | 100 | 5-9 | 150 | 125 | | | • | • | ****** | 0,60 | • | • | • | 0,09 | 46 | 78 | 84 | | A |
| Universal-6 65 | | • | • | • | • | • | | | | 35 | | • | 112 | 6-9 | 150 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,07 | 24 | 79 | 84 | | A |
| Universal-6 70 | | • | • | • | • | • | | | | 40 | | • | 115 | 7-10 | 180 | 125 | | | • | • | ******* | 0,50 | • | • | • | 0,09 | 36 | 77 | 84 | | A |
| Universal-6 75 | | • | • | • | • | • | | | | 40 | | • | 126 | 7-11 | 180 | 125 | | | • | • | ******* | 0,50 | • | • | • | 0,09 | 27 | 76 | 83 | | A |
| Universal-6 80 | | • | • | • | • | • | | | | 40 | | • | 128 | 8-12 | 180 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,06 | 27 | 76 | 83 | | A |
| Universal-6 85 | | • | • | • | • | • | | | | 50 | | • | 141 | 8-12 | 180 | 125 | | | • | • | ******* | 0,50 | • | • | • | 0,10 | 20 | 77 | 84 | | A |
| **Unilux-6** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Unilux-6 40 | | • | • | • | • | • | | | | 20 | | • | 68 | 4-6 | 130 | 80 | | | • | • | ******* | 0,50 | • | • | • | 0,08 | 39 | 76 | 83 | • | A |
| Unilux-6 43 | | • | • | • | • | • | | | | 30 | | • | 97 | 6-8 | 130 | 80 | | | • | • | ******* | 0,30 | • | ** | ** | 0,05 | 20 | 79 | 84 | | A |
| Unilux-6 45 | | • | • | • | • | • | | | | 20 | | • | 87 | 5-7 | 130 | 80 | | | • | • | ******* | 0,40 | • | ** | ** | 0,09 | 20 | 76 | 81 | | A |
| Unilux-6 52 | | • | • | • | • | • | | | | 30 | | • | 79 | 5-8 | 130 | 80 | | | • | • | ******* | 0,40 | • | • | • | 0,06 | 34 | 78 | 85 | • | A |
| Unilux-6 55 | | • | • | • | • | • | | | | 30 | | • | 93 | 6-9 | 130 | 80 | | | • | • | ******* | 0,40 | • | • | • | 0,05 | 34 | 75 | 82 | • | A |
| Unilux-6 65 | | • | • | • | • | • | | | | 40 | | • | 90 | 7-9 | 150 | 125 | | | • | • | ******* | 0,60 | • | • | • | 0,08 | 40 | 75 | 82 | • | A |
| Unilux-6 67 | | • | • | • | • | • | | | | 40 | | • | 109 | 7-10 | 150 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,07 | 19 | 75 | 82 | • | A |
| Unilux-6 70 | | • | • | • | • | • | | | | 45 | | • | 105 | 8-12 | 150 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,07 | 25 | 76 | 83 | • | A |
| Unilux-6 75 | | • | • | • | • | • | | | | 50 | | • | 107 | 9-13 | 150 | 125 | | | • | • | ******* | 0,50 | • | • | • | 0,06 | 40 | 75 | 82 | • | A |
| Unilux-6 80 | | • | • | • | • | • | | | | 50 | | • | 123 | 8-11 | 150 | 125 | | | • | • | ******* | 0,40 | • | • | • | 0,09 | 17 | 76 | 83 | • | A |
| Unilux-6 265 Left / Right | | • | | • | | • | | | | 40 | | • | 114 | 7-9 | 150 | 125 | | | • | • | ******* | 0,60 | • | ** | ** | 0,10 | 39 | 75 | 82 | | A |
| Unilux-6 265 Three sided | | • | | • | | • | | | | 40 | | • | 112 | 7-9 | 150 | 125 | | | • | • | ******* | 0,60 | • | ** | ** | 0,10 | 39 | 75 | 82 | | A |
| Unilux-6 270 Left / Right | | • | | • | | • | | | | 45 | | • | 138 | 9-12 | 180 | 125 | | | • | • | ******* | 0,40 | • | ** | ** | 0,09 | 19 | 75 | 82 | | A |
| Unilux-6 270 Three sided | | • | | • | | • | | | | 45 | | • | 135 | 9-12 | 180 | 125 | | | • | • | ******* | 0,40 | • | ** | ** | 0,09 | 19 | 75 | 82 | | A |

[1] Not available for Belgium.
Pas disponible en Belgique.

| | Door | | Frame | | | | | | | Max length wood logs | Interior | | Weight | Output | Gas flue outlet | Air supply | Air box | Convection casing | Convection fan system | Extended adjustable legs | Standard | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | modern door | 6-door | frameless | classic frame | insert frame | built-in frame | 3-sided frame 35 mm. | 4-sided frame 35 mm. | 3-sided frame 42 mm. | 4-sided frame 42 mm. | max. cm. | vermiculite panels | ceramic concrete | cast iron | kg. aprox. - without log store. | kg. aprox. - with log store | kg. aprox. - included fan and extended adjustable legs) | kW | Ø (mm.) | Ø (mm.) | option | standard | option | optional system | option | CE - EN 13229 | Flamme Verte | Flamme Verte Indice I' | 1.BImSchV | VKF-LRV11 | Smoke Control Areas | CO (vol%) | fine particles (mg/m³) | efficiency (%) | system efficiency, approx.* (%) | energy efficiency class |
| **Cuatro-3** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cuatro-3 57 | • | | • | | | | • | • | | | 50 | | • | | 147 | | | 9-13 | 180 | 125 | | • | | • | • | • | ******* | 0,40 | • | | • | 0,08 | 20 | 80 | 83 | A+ |
| Cuatro-3 70 | • | | • | | | | • | • | | | 50 | | • | | 145 | | | 8-11 | 180 | 125 | | • | | • | • | • | ******* | 0,40 | • | | • | 0,08 | 22 | 79 | 83 | A |
| Cuatro-3 75 | • | | • | | | | • | • | | | 50 | | • | | 138 | | | 10-14 | 180 | 125 | | • | | • | • | • | ******* | 0,50 | • | | • | 0,08 | 39 | 78 | 81 | A |
| Cuatro-3 80 | • | | • | | | | • | • | | | 60 | | • | | 160 | | | 10-15 | 200 | 125 | | • | | • | • | • | ******* | 0,50 | • | | • | 0,07 | 40 | 79 | 83 | A |
| Cuatro-3 90 | • | | • | | | | • | • | | | 50 | | • | | 161 | | | 13-18 | 200 | 125 | | • | | • | • | • | ******* | 0,50 | • | | • | 0,07 | 37 | 76 | 79 | A |
| **Falcon** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Falcon 73/63 | | | • | | | • | | | • | • | 40 | | | • | 218 | | 236 | 8-14 | 200 | 125 | • | | • | | • | • | ** | 0,40 | • | ** | ** | 0,07 | 24 | 75 | 83 | A |
| **BOX** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BOX 40 | | | | | | | | | | | 20 | | • | | 105 | 142 | | 4-6 | 130 | 80 | | | | | | • | ******* | 0,50 | • | ** | ** | 0,08 | 39 | 76 | 83 | A |
| BOX 43 | | | | | | | | | | | 30 | | • | | 137 | 185 | | 6-8 | 130 | 80 | | | | | | • | ******* | 0,30 | • | ** | ** | 0,05 | 20 | 79 | 86 | A |
| BOX 45 | | | | | | | | | | | 20 | | • | | 127 | 155 | | 5-7 | 130 | 80 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,09 | 20 | 76 | 83 | A |
| BOX 52 | | | | | | | | | | | 30 | | • | | 115 | 156 | | 5-9 | 130 | 80 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,06 | 34 | 78 | 85 | A |
| BOX 55 | | | | | | | | | | | 30 | | • | | 139 | 180 | | 6-9 | 130 | 80 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,05 | 34 | 75 | 82 | A |
| BOX 65 | | | | | | | | | | | 40 | | • | | 132 | 178 | | 7-9 | 150 | 125 | | | | | | • | ******* | 0,60 | • | ** | ** | 0,08 | 40 | 75 | 82 | A |
| BOX 67 | | | | | | | | | | | 40 | | • | | 158 | 204 | | 7-10 | 150 | 125 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,07 | 19 | 75 | 82 | A |
| BOX 70 | | | | | | | | | | | 45 | | • | | 152 | 200 | | 8-12 | 150 | 125 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,07 | 25 | 76 | 83 | A |
| BOX 75 | | | | | | | | | | | 50 | | • | | 146 | 196 | | 9-13 | 150 | 125 | | | | | | • | ******* | 0,50 | • | ** | ** | 0,06 | 40 | 75 | 82 | A |
| BOX 80 | | | | | | | | | | | 50 | | • | | 175 | 226 | | 8-11 | 150 | 125 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,09 | 17 | 76 | 83 | A |

| | Porte | | Cadre | | | | | | | Taille des bûches | Intérieur | | Poids | | Puissance | Diamètre de connexion au conduit | Entrée d'air | Boîte de raccordement | Caisse de convection | Ventilateur de convection | Pieds réhaussés | Normes | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | porte moderne | porte 6 | sans cadre | cadre classique | cadre de profondeur | cadre encastrable | 3 côtés 35 mm. | 4 côtés 35 mm. | Hidden Door+ 8 cm. | Hidden Door+ 8 cm. & extérieur en pierre | max. cm. | plaques de vermiculite | béton céramique | fonte | kg. aprox - sans socle bûcher | kg. aprox. - avec socle bûcher | kg. environ - ventilateur et pieds réhaussés inclus | kW | Ø (mm.) | Ø (mm.) | option | standard | option | option | option | option | CE - EN 13229 | Flamme Verte | Flamme Verte Indice I' | 1.BImSchV | VKF-LRV11 | Smoke Control Areas | CO (vol%) | poussières fines (mg/m³) | rendement de certification (%) | rendement de système* (%) | Classe d'efficacité énergétique |
| **Cuatro-3** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cuatro-3 57 | • | | • | | | | • | • | | | 50 | | • | | 147 | | | 9-13 | 180 | 125 | | • | | • | • | • | ******* | 0,40 | • | | • | 0,08 | 20 | 80 | 83 | A+ |
| Cuatro-3 70 | • | | • | | | | • | • | | | 50 | | • | | 145 | | | 8-11 | 180 | 125 | | • | | • | • | • | ******* | 0,40 | • | | • | 0,08 | 22 | 79 | 83 | A |
| Cuatro-3 75 | • | | • | | | | • | • | | | 50 | | • | | 138 | | | 10-14 | 180 | 125 | | • | | • | • | • | ******* | 0,50 | • | | • | 0,08 | 39 | 78 | 81 | A |
| Cuatro-3 80 | • | | • | | | | • | • | | | 60 | | • | | 160 | | | 10-15 | 200 | 125 | | • | | • | • | • | ******* | 0,50 | • | | • | 0,07 | 40 | 79 | 83 | A |
| Cuatro-3 90 | • | | • | | | | • | • | | | 50 | | • | | 161 | | | 13-18 | 200 | 125 | | • | | • | • | • | ******* | 0,50 | • | | • | 0,07 | 37 | 76 | 79 | A |
| **Falcon** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Falcon 73/63 | | | • | | | • | | | • | • | 40 | | | • | 218 | | 236 | 8-14 | 200 | 125 | • | | • | | • | • | ** | 0,40 | • | ** | ** | 0,07 | 24 | 75 | 83 | A |
| **BOX** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BOX 40 | | | | | | | | | | | 20 | | • | | 105 | 142 | | 4-6 | 130 | 80 | | | | | | • | ******* | 0,50 | • | ** | ** | 0,08 | 39 | 76 | 83 | A |
| BOX 43 | | | | | | | | | | | 30 | | • | | 137 | 185 | | 6-8 | 130 | 80 | | | | | | • | ******* | 0,30 | • | ** | ** | 0,05 | 20 | 79 | 86 | A |
| BOX 45 | | | | | | | | | | | 20 | | • | | 127 | 155 | | 5-7 | 130 | 80 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,09 | 20 | 76 | 83 | A |
| BOX 52 | | | | | | | | | | | 30 | | • | | 115 | 156 | | 5-9 | 130 | 80 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,06 | 34 | 78 | 85 | A |
| BOX 55 | | | | | | | | | | | 30 | | • | | 139 | 180 | | 6-9 | 130 | 80 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,05 | 34 | 75 | 82 | A |
| BOX 65 | | | | | | | | | | | 40 | | • | | 132 | 178 | | 7-9 | 150 | 125 | | | | | | • | ******* | 0,60 | • | ** | ** | 0,08 | 40 | 75 | 82 | A |
| BOX 67 | | | | | | | | | | | 40 | | • | | 158 | 204 | | 7-10 | 150 | 125 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,07 | 19 | 75 | 82 | A |
| BOX 70 | | | | | | | | | | | 45 | | • | | 152 | 200 | | 8-12 | 150 | 125 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,07 | 25 | 76 | 83 | A |
| BOX 75 | | | | | | | | | | | 50 | | • | | 146 | 196 | | 9-13 | 150 | 125 | | | | | | • | ******* | 0,50 | • | ** | ** | 0,06 | 40 | 75 | 82 | A |
| BOX 80 | | | | | | | | | | | 50 | | • | | 175 | 226 | | 8-11 | 150 | 125 | | | | | | • | ******* | 0,40 | • | ** | ** | 0,09 | 17 | 76 | 83 | A |

* Calculated for average room
* Calcul selon une pièce de taille moyenne.

** Up for approval
** Homologation en cours

**For more details see product manual www.barbas.com**

**Pour plus de détails, télécharger les notices sur www.barbas.com**